TECHNICAL DATA SHEET

Micro S Automatic



Lateral Installation: 3"-10" | DN75 - 250

DESCRIPTION

The proven features of the MICRO series combined with even better flexibility in pipe bends and a range of use in even smaller pipes - this is what distinguishes the MICRO S automatic from its competition. With its powerful cutting motor, the lateralconnection cutter removes any deposits and is a reliable tool when opening and reopening lateral connections after liner rehabilitation, quickly and effectively. In conjunction with the axial feed, the flexibility in pipe bends ensures that the cutter can reach any location. The color camera with LED illumination guarantees exact positioning. Precise and without loss of time, the axial feeding function can be operated easily and conveniently at the cutting spot.

PRODUCT INFORMATION

- Automatic and manual feed, climbing and creeping function (4" | 100 mm axial feed)
- · Outer diameter of the cutter module is just 60 mm
- 164 ft | 50 m supply hose on cable reel
- Integrated color camera with permanent air cleaning and additional water cleaning
- Powerful air-operated cutting motor (also usable for stone and concrete)
- Very precise control of the cutter by optional
 2 Joysticks
- Expansions 8"-10" | DN200-DN250 included
- Mini PC and video software included water cleaning

OPTIONAL

- 16' and 32' | 5 m and 10 m extension cable for control unit
- Meter counting





REV. 07-17-2024 (877) 426-5948 maxlinerusa.com