

United Glass RP & United Glass PS - PP Coated

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	United Glass RP & United Glass PS - PP Coated	
Trade Name	United Glass RP & United Glass PS - PP Coated	
Company	United Felts, 450 College Drive, Martinsville, VA 24112	
Company Contact	Mark Chandler	
Company Phone	• 276-656-1904	
Emergency	• 276-656-1904	

2. HAZARDS IDENTIFICATION

Hazard Designation	Not classified as a hazardous material.
Potential Health Hazards	During decomposition or combustion, the product can cause irritation
	to eyes, skin, or respiratory tract. As a delayed effect, sensitization to
	isocyanates may occur.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Polyetyhlene Terephthalate	25038-59-9	54 - 86
Fiberglass, continuous filament, non-respirable	65997-17-3	20 - 40
1-propene, polymer with ethene	9010-79-1	4 - 38
Titanium Dioxide	13463-67-7	< 3

This product may have been produced with Titanium Dioxide. Titanium Dioxide is not water soluble and is encapsulated. It is not extracted or released in normal processing. Therefore, Titanium in this material does not represent a hazard in normal handling, processing use and disposal.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if applicable are listed in Section 8.

REV. 05-09-2024 (276) 656-1904 www.unitedfelts.com

UNITED GLASS RP & UNITED GLASS PS - PP COATED **SAFETY DATA SHEET**



4. FIRST AID MEASURES

Inhalation	In case of upper respiratory tract irritation:
	Move to fresh air.
	If symptoms persist, call a physician.
Skin contact	In case of irritation:
	• Wash off immediately with soap and <u>cold</u> water.
	• Do not use warm water because this will open up the pores of the skin,
	which will cause further penetration of the fibers.
	• Do not rub or scratch affected areas.
	Remove contaminated clothing.
	• If skin irritation persists, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at
	least 15 minutes.
	Do not rub or scratch eyes.
	If eye irritation persists, call a physician.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing	• Water	
	• Water	
Media	• Foam	
	Dry Chemical	
Hazardous Decombustion	Carbon Dioxide (CO ₂)	
Products	Carbon Monoxide (CO)	
	Hydrogen Cyanide (HCN)	
	Oxides of Nitrogen	
	Hydrocarbons	
	Diisocyanate	
Special Protective	Positive pressure self-contained breathing apparatus and full	
Equipment	firefighting protective gear.	

6. ACCIDENTAL RELEASE MEASURES

Spill Clean-up Methods	Not applicable.

7. HANDLING AND STORAGE

Usage Precautions	Not applicable.	
Storage Precautions	Not applicable.	

UNITED GLASS RP & UNITED GLASS PS - PP COATED SAFETY DATA SHEET



8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective Equipment	
Ventilation	Not applicable.
Respirators	Not applicable.
Protective gloves	• Yes
Eye protection	Safety glasses with side-shields.
General protective and hygienic measures	 Standard industry safety and hygiene principles should be exercised Wash hands before breaks and immediately after handling the product.

If a component is disclosed in Section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m³ total	IDLH: 5000 mg/m³
13463-67-7		dust (vacated)	TWA: 2.4 mg/m ³ CIB 63 fine
		TWA: 10 mg/m³ total	TWA: 0.3 mg/m ³ CIB 63
		dust	ultrafine, including engineered
			nanoscale

9. PHYSICAL & CHEMICAL PROPERTIES

Physical state	Polyurethane coated liner
Color	• White
Odor	• Faint
Melting point - felt	• 260 °C
Melting point - coating	• > 177 °C
Softening point - fiberglass	• >800 °C
Melting point - fiberglass	Non applicable.
Density - felt	• 150 - 200 Kg/m³
Density - coating	• 1100 - 1300 Kg/m³
Density (molten glass)	• 2.6 (water = 1)
Flammability	Non applicable.

10. STABILITY & REACTIVITY

Stability	Normally Stable.
Conditioning/Materials to be avoided	Excessive heatOrganic solvents
Hazardous decomposition product(s)	 Carbon Dioxide (CO₂), Carbon Monoxide (CO), Hydrogen Cyanide (HCN), Oxides of Nitrogen, Hydrocarbons and Diisocyanate, are all anticipated at levels above trace.

11. TOXICOLOGICAL INFORMATION

Health Warnings	 No health risk at ambient temperatures. Elevated temperatures may cause this product to emit irritating
	vapors. • Dust and fibers may cause mechanical irritation to the eyes and skin.

UNITED GLASS RP & UNITED GLASS PS - PP COATED SAFETY DATA SHEET



12. ECOLOGICAL INFORMATION

Environmental Hazards	Not biologically degradable.	
	Bioaccumulation improbable.	
	Generally not hazardous to water.	

13. DISPOSAL CONSIDERATIONS

Disposal Methods	Dispose of waste by incineration or in landfill in accordance with local regulations.
	Fiberglass waste is a nonhazardous waste according to the European Waste Code number 101103.

14. TRANSPORT INFORMATION

Not classified as a dangerous cargo.

15. REGULATORY INFORMATION

Designation according	• No
to european commission	• Ob
guidelines	• The

- known regulations related to this product.
- serve the local safety regulations for handling chemicals.
- e fiberglass is not hazardous according to European Directive 99/45/EC, 67/548/EEC and their latest amendment.

16. OTHER INFORMATION

This data is based on our present knowledge. However, they shall not be constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

NFPA Hazard Rating	Health	Fire	Reactivity
	1	1	0
	Slight	Slight	Minimal
HMIS Hazard Rating	Health	Fire	Reactivity
	1	1	0
	Slight	Slight	Minimal